

CAM & GROOVE COUPLINGS

TYPE D: COUPLER FEMALE THREADED

ND	Inch	Thread EN ISO 228-1	Material	Coupler seal	Handles	Weight/pc Kg	Reference
15	1/2"	G 1/2	Aluminium	NBR	1	0.06	VLDA013
20	3/4"	G 3/4	Aluminium	NBR	2	0.12	VLDA019
25	1"	G 1	Aluminium	NBR	2	0.16	VLDA025
32	1.1/4"	G 1.1/4	Aluminium	NBR	2	0.28	VLDA032
40	1.1/2"	G 1.1/2	Aluminium	NBR	2	0.32	VLDA038
50	2"	G 2	Aluminium	NBR	2	0.36	VLDA050
65	2.1/2"	G 2.1/2	Aluminium	NBR	2	0.47	VLDA063
80	3"	G 3	Aluminium	NBR	2	0.73	VLDA075
100	4"	G 4	Aluminium	NBR	2	1.21	VLDA100
125	5"	G 5	Aluminium	NBR	2	1.40	VLDA125
150	6"	G 6	Aluminium	NBR	2	2.16	VLDA150
200	8"	G 8	Aluminium	NBR	4	2.60	VLDA200
15	1/2"	G 1/2	Stainless steel	NBR	1	0.13	VLDR013
20	3/4"	G 3/4	Stainless steel	NBR	2	0.23	VLDR019
25	1"	G 1	Stainless steel	NBR	2	0.31	VLDR025
32	1.1/4"	G 1.1/4	Stainless steel	NBR	2	0.49	VLDR032
40	1.1/2"	G 1.1/2	Stainless steel	NBR	2	0.55	VLDR038
50	2"	G 2	Stainless steel	NBR	2	0.70	VLDR050
65	2.1/2"	G 2.1/2	Stainless steel	NBR	2	1.00	VLDR063
80	3"	G 3	Stainless steel	NBR	2	1.30	VLDR075
100	4"	G 4	Stainless steel	NBR	2	2.14	VLDR100
125	5"	G 5	Stainless steel	NBR	2	3.54	VLDR125
150	6"	G 6	Stainless steel	NBR	2	4.61	VLDR150
15	1/2"	G 1/2	Brass	NBR	1	0.16	VLDM013
20	3/4"	G 3/4	Brass	NBR	2	0.22	VLDM019
25	1"	G 1	Brass	NBR	2	0.32	VLDM025
32	1.1/4"	G 1.1/4	Brass	NBR	2	0.46	VLDM032
40	1.1/2"	G 1.1/2	Brass	NBR	2	0.54	VLDM038
50	2"	G 2	Brass	NBR	2	0.67	VLDM050
65	2.1/2"	G 2.1/2	Brass	NBR	2	0.94	VLDM063
80	3"	G 3	Brass	NBR	2	1.40	VLDM075
100	4"	G 4	Brass	NBR	2	2.09	VLDM100
125	5"	G 5	Brass	NBR	2	2.58	VLDM125
150	6"	G 6	Brass	NBR	2	5.02	VLDM150
20	3/4"	G 3/4	Bronze	NBR	2	0.23	VLDB019
25	1"	G 1	Bronze	NBR	2	0.35	VLDB025
32	1.1/4"	G 1.1/4	Bronze	NBR	2	0.50	VLDB032
40	1.1/2"	G 1.1/2	Bronze	NBR	2	0.66	VLDB038
50	2"	G 2	Bronze	NBR	2	0.78	VLDB050
65	2.1/2"	G 2.1/2	Bronze	NBR	2	0.95	VLDB063
80	3"	G 3	Bronze	NBR	2	1.63	VLDB075
100	4"	G 4	Bronze	NBR	2	2.42	VLDB100
15	1/2"	G 1/2	Polypropylene	EPDM	2	0.07	VLDP013
20	3/4"	G 3/4	Polypropylene	EPDM	2	0.08	VLDP019
25	1"	G 1	Polypropylene	EPDM	2	0.13	VLDP025
32	1.1/4"	G 1.1/4	Polypropylene	EPDM	2	0.21	VLDP032
40	1.1/2"	G 1.1/2	Polypropylene	EPDM	2	0.23	VLDP038
50	2"	G 2	Polypropylene	EPDM	2	0.27	VLDP050
80	3"	G 3	Polypropylene	EPDM	2	0.50	VLDP075
100	4"	G 4	Polypropylene	EPDM	3	0.75	VLDP100



Coupling standard: Federal Mil A-A-59326A
 Female thread: EN ISO 228-1, BSP
 ANSI B 1.20.1, NPT on request
 Stainless steel: AISI 316 - EN 1.4401
 ND 200 stainless steel on request available